



SPECIFICATIONS FOR RUSSIAN GAS OIL 0.2/62 GOST 305-82

COMPONENT	UNIT	TEST RESULTS	
		MIN	MAX
GENERAL REPORTING			
DENSITY AT 20 DEG. C	Kg / m3		0.870
COLOUR		1.0	2.0
FLASH POINT PMCC	DEG. C	57	66
KINEMATICS VISCOCITY AT 20 DEG. C	cSt	3.0	6.0
POUR POINT	DEG. C	(*)	-10.0
CLOUD POINT	DEG. C	(*)	-5.0
MERCAPTAN SULPHUR MARGIN	%		0.01
ACIDITY	Mg / 100 cm3		5
IODINE NUMBER	G/100g		6
ASH	% Wt		0.01
TOTAL SULPHUR	% Wt		0.5
COPPER CORROSION (3HRS @ 50 DEG C)			1A
CCR ON 5% RESIDUE	% Wt		0.20
CETANE INDEX		45	
DISTILLATION RANGE			
50 % RECOVERY VOLUME	DEG. C		280
90 % RECOVERY VOLUME	DEG. C		360
BACTERIA MBC	Fiber/Lt		500
BACTERIA CFU	Fiber/Lt		1000

(*) SUMMER FROM MARCH TO OCTOBER (PP – 5,0 DEGREES C)(CP – 5,0 DEGREES C)

(*) WINTER FROM NOVEMBER TO FEBRUARY (PP -10.0 DEGREES C)(CP – 5,0 DEGREES C)